



ITEM	PART NUMBER
A	320-10240
B	14963286
C	14947663
D	580-10244
E	580-10019





- AUXILIARY VIEW -
FASTENING DIMENSIONS




C - (COPPER) PROCESS TUBE
GAGE I.D. TO 6.45-6.55
x 15.00-17.00 DEEP.

D - (COPPER) DISCHARGE TUBE
GAGE I.D. TO 6.45-6.55
x 15.00-17.00 DEEP.




- NOTES:
- 1- IF SPECIFIED IN BM. ASSEMBLE PARTS AS SHOWN.
 - 2- SEE SPEC. "A-B" & A-C FOR PROCESS.
 - 3- THERE CAN BE NO CREASES IN THE TUBES. (CREASES ARE SIGNS OR MARKS THAT ARE IN SOMETHING THAT BENDS)
 - 4- AFTER THE FOLDS IN THE TUBES, CANNOT BE ACCELERATED TO AREA EXCEEDING 30%.
 - 5- TUBES OF SUCTION, DISCHARGE AND PROCESS MUST BE FREE OF INK ON 15.8mm (5/8") FROM TOP OF THE TUBES AS SPEC. T.P.Co. A-B4.
 - 6- FOR SUPPLIER ENVIRONMENTAL REGULATORY REQUIREMENTS, SEE TECUMSEH GLOBAL SPEC. 08.

AB
AF



UNITS: mm
DRAWING SIZE: A2

0. A. SYMBOLS AS
PROCEDURE 2.01.031
TECUMSEH OF BRAZIL
★ = CATEGORY I
▲ = CATEGORY III
■ = CATEGORY III
= CATEGORY IV



Tecumseh

NAME SALES COMPRESSOR		PART NO. DCAE681	
DATE 20/06/12		SCALE 1:2	
REF.		PAGE 1/1	
FAMILY AE2			