



ITEM	PART NUMBER
A	320-10240
B	14963286
C	14947663
D	580-10244
E	580-10019





- AUXILIARY VIEW -
FASTENING DIMENSIONS



C - (COPPER) PROCESS TUBE
GAGE I.D. TO 6.45-6.55
× 15.00-17.00 DEEP.

E - (COPPER) SUCTION TUBE
GAGE I.D. TO 8.00-8.10
× 15.00-17.00 DEEP.

D - (COPPER) DISCHARGE TUBE
GAGE I.D. TO 6.45-6.55
× 15.00-17.00 DEEP.



NOTES:

- IF SPECIFIED IN BM. ASSEMBLE PARTS AS SHOWN.
- SEE SPEC. "A-B" & A-C FOR PROCESS.
- THERE CAN BE NO CREASES IN THE TUBES. (CREASES ARE SIGNS OR MARKS THAT ARE IN SOMETHING THAT BENDS)
- AFTER THE FOLDS IN THE TUBES, CANNOT BE ACCELERATED TO AREA EXCEEDING 30%.
- TUBES OF SUCTION, DISCHARGE AND PROCESS MUST BE FREE OF INK ON 15.8mm (5/8") FROM TOP OF THE TUBES AS SPEC. T.P.Co. A-B4.
- FOR SUPPLIER ENVIRONMENTAL REGULATORY REQUIREMENTS, SEE TECUMSEH GLOBAL SPEC. 08.

AB
AF

THIRD ANGLE PROJECTION
UNITS: mm
DRAWING SIZE: A2
0. A. SYMBOLS AS PROCEDURE 2.01.031 TECUMSEH OF BRAZIL
★ = CATEGORY I
▲ = CATEGORY III
■ = CATEGORY III
■ = CATEGORY IV



Tecumseh

NAME	PART NO.
SALES COMPRESSOR	DCAE681
SCALE	PAGE
1:2	1/1
DATE	REF.
20/06/12	
FAMILY	AE2