



ITEM	PART NUMBER
A	320-10156
B	14963286
C	14947663
D	580-10244
E	14963572





- AUXILIARY VIEW -
FASTENING DIMENSIONS



E - (COPPER) SUCTION TUBE
GAGE I.D. TO 9.6-9.7
× 15.00-17.00 DEEP.

D - (COPPER) DISCHARGE TUBE
GAGE I.D. TO 6.45-6.55
× 13.00-15.00 DEEP.

C - (COPPER) PROCESS TUBE
GAGE I.D. TO 6.45-6.55
× 15.00-17.00 DEEP.



- NOTES:
- 1- IF SPECIFIED IN BM. ASSEMBLE PARTS AS SHOWN.
 - 2- SEE SPEC. "A-B" & A-C FOR PROCESS.
 - 3- THERE CAN BE NO CREASES IN THE TUBES. (CREASES ARE SIGNS OR MARKS THAT ARE IN SOMETHING THAT BENDS)
 - 4- AFTER THE FOLDS IN THE TUBES, CANNOT BE ACCELERATED TO AREA EXCEEDING 30%.
 - 5- TUBES OF SUCTION, DISCHARGE AND PROCESS MUST BE FREE OF INK ON 15.8mm (5/8") FROM TOP OF THE TUBES AS SPEC. T.P.Co. A-B4.
 6. FOR SUPPLIER ENVIRONMENTAL REGULATORY REQUIREMENTS, SEE TECUMSEH GLOBAL SPEC. 08.

AC

AD

AG

THIRD ANGLE PROJECTION

UNITS: mm

DRAWING SIZE: A2

★ = CATEGORY I
▲ = CATEGORY II
■ = CATEGORY III
● = CATEGORY IV



tecumseh

NAME				PART NO.	
SALES COMPRESSOR				DCAE199	
DWN.	CK.	APR.	SCALE	1:2	PAGE 1/1
J. BARBANO	ANDRE MARTINEZ	WALTER CORREA	REF.		
DATE	22/09/11				
				FAMILY	AE2