

	DIM. W	DIM. X	DIM. Y
WITH 3.875 (98.4) LONG CAPACITOR	1.453-1.703 36.9-43.3	4.078-4.141 103.6-105.2	_____
WITH 1.438 (36.5) DIA. CAPACITOR	_____	_____	1.969-2.031 50.0-51.6
WITH 4.875 (123.8) LONG CAPACITOR	1.953-2.203 49.6-56.0	5.078-5.141 129.0-130.6	_____
WITH 1.813 (46.1) DIA. CAPACITOR	_____	_____	2.344-2.406 59.5-61.1

▲ .750-.760 DIA. (4)-HOLES
19.1-19.3

SUCTION - COPPER
O.D. - .3105-.3145 (7.9-8.0)
WALL - .032-.038 (0.8-1.0)
END I.D. - .315-.318 (8.0-8.1)
× .865-.885 (22.0-22.5)
PLUG - .3

(N)
PROCESS - COPPER
O.D. - .3105-.3145 (7.9-8.0)
I.D. - .254-.258 (6.5-6.6)
PLUG. -2

1. IF SPECIFIED ON BILL OF MATERIAL
ASSEMBLE THESE PARTS AS SHOWN.
2. SEE SPEC. "A-B" & "A-C" FOR PROCESSING.

DIMENSIONS = $\frac{\text{INCHES}}{\text{MILLIMETERS}}$ OR INCHES (MILLIMETERS)

Q.A. SYMBOLS

★	= CATEGORY I
▲	= CATEGORY II
■	= CATEGORY III
□	= CATEGORY IV

[illegible]