



NOTE !
 1. IF SPECIFIED ON BILL OF MATERIAL ASSEMBLE THESE PARTS AS SHOWN.
 2. PLACEMENT OF HEATER LEADS - THRU BOTTOM HOLE IN FENCE ON COMPRESSOR WITH COVER, OR THRU BALE STRAP HOLE ON COMPRESSOR WITHOUT COVER.

MANUFACTURING NOTES !
 1. SEE DWG. #AHT-17 FOR ASS'Y. OF DISCH. CONN. TUBE & LOWER SHOCK LOOP IN LOWER HOUSING.
 2. SUCTION TUBE MUST NOT EXTEND BEYOND INSIDE SURFACE OF HOUSING.
 3. SEE SPEC. "A-B" & "A-C" FOR PROCESSING.

DIMENSIONING = INCHES OR MILLIMETERS (MILLIMETERS)

O.A. SYMBOLS

- ★ = CATEGORY I
- ▲ = CATEGORY II
- = CATEGORY III
- = CATEGORY IV

G	28080-3	A	HA605-13
H	26222-1	B	HA604-6
		C	34602
		D	34600
		E	34467
		F	26223

BT	5A	EC2352	T.M.G	12APR07
BS	5A	#241251-000	T.M.G	12DEC01
BR	-	REVISED TO V16	A.S.C	6/1/89
BP	D2	#219823	O.A.	SYMBOLS ADDED
BN	D2	#217685	J.F.J.	2/23/88
B	M	REDRAWN	J.F.J.	8/13/88
		NO CHANGE	HB	
		#212377		4-29-87

DIS.CODE	NAME	SCALE	THIS PRINT SUPERSEDES ALL PRINTS PRIOR TO
	SALES COMPRESSOR	1/2" = 1"	
MATERIAL	NOTED	PART NO.	DCAG-003