



WARNING- WIRING DIAGRAM MUST BE FOLLOWED AS SHOWN. ANY MISWIRING CAN CAUSE SERIOUS ELECTRICAL HAZARD AND POTENTIAL DAMAGE OR RUPTURE OF COMPONENT ELECTRICAL PARTS.

- NOTES:
- ASSEMBLE THESE PARTS AS SHOWN IF SPECIFIED ON B/M.
 - IDENTIFIED CONDUCTOR MAYBE WHITE OR RIBBED (115 VOLT ONLY-NEUTRAL).
 - IF TWO RUN CAPACITOR ARE REQUIRED HOOKUP AS SHOWN.
 - COMPRESSOR UNIT GROUND SCREW IS NOT PROVIDED BY T.P.CO.

115 OR 230 V.-SCHEMATIC WIRING DIAGRAM - CSR OR CSR START CAPACITOR ASSIST (REF. DWG. MD472-35)

115 OR 230 V.-SCHEMATIC WIRING DIAGRAM - PSC (REF. DWG. MD472-4)

AJ - 115 OR 230 VOLT - PSC
 AJ - 115 OR 230 VOLT - CSR OR CSR START CAPACITOR ASSIST AJ

ENGLISH	
	Q.A. SYMBOLS
	☆ = CATEGORY I
	△ = CATEGORY II
	□ = CATEGORY III
	○ = CATEGORY IV

Banner User: ecrack Part/Rev: 01-deaj4_y-c.prt Date: 19-May-06 Time: 08:14

#244142-000 REDRAWN, & REVISED ORIENTATION OF LEAD WIRE.	U	7F	3F	DATE	DATE	DIS.CODE	NAME	SCALE	THIS PRINT SUPERSEDES ALL PRINTS PRIOR TO
							ELECTRICAL HOOKUP	1:1 & NOTED	
							TECUMSEH PRODUCTS CO. TECUMSEH, MICHIGAN		DRAWING NO.
							NOTED		DEAJ4
						DRAWING No.	REVISION LEVEL:		
						MO888-08	REL		